

# SWASHEQUIPMENT™

- Makes vehicles easier to clean and bug splatter easier to remove, keeping surfaces cleaner for longer
- Creates a glossy finish that keeps equipment looking new for longer
- Decreases fire risk due to dust accumulation
- Decreases drying and out-of-service time for vehicles and equipment
- Improves farm biosecurity by making manure, litter and other organic matter easy to remove
- Can be applied to all surfaces (excluding seats and foot pedals) with no drying or rinsing required



## PRODUCT DATA SHEET

Vehicles and farm equipment face a barrage of daily insults that impact their appearance, level of cleanliness, and can even pose potential biosecurity and fire risks. When applied to glass and painted surfaces, SWASHEQUIPMENT™ keeps surfaces cleaner and looking new for longer.



## HOW IT WORKS

The SWASHEQUIPMENT™ formula contains three separate agents that work as a multi-faceted, single application solution.

### Prevents Accumulation



An anti-static agent reduces static charge to prevent dust from accumulating on surfaces which also decreases fire risk.

### Forms a Barrier



A silicone-based film-forming agent creates a strong barrier that protects surfaces from environmental insults, such as dirt, grime, road salts and bug splatter, while maintaining a glossy finish that is only removed under high-pressure spray (150 psi+).

### Repels Water



The hydrophobic agent in SWASHEQUIPMENT™ repels moisture to speed up drying time.

## APPLICATIONS



SWASHEQUIPMENT™ is ideal for use on farm vehicles and equipment, as well as exterior surfaces, boats and ATVs.

- Tractors
- Trucks and cars
- Mowers (decrease grass and dirt buildup and easily rinse off grass residue)
- Combines
- Tillers/deckers/windrowers
- Hatchery tray washers
- Milking equipment
- Boats (helps remove algae stains)
- Driveways/sidewalks/masonry (helps remove algae stains for a cleaner appearance)
- ATVs (make mud easy to remove)
- Live haul coops and transport trailers

*\* Product is not suitable for use to treat interior vehicle seats and vehicle-operating pedals.*

## DIRECTIONS FOR USE

### Precautions

Do not apply to vehicle seats or operating pedals.

### Application Instructions

1. Pre-clean all surfaces to be treated.
2. Spray all surfaces with SWASHEQUIPMENT™ at a dilution rate of 1:3 (1 gal SWASHEQUIPMENT™ per 3 gallons of water) using a low pressure or foamer sprayer.
3. Apply registered disinfectant, if using.
4. Allow to air dry.

*“If you want to have equipment that’s easier to clean and keep clean this is the product to use. I sprayed my round baler before season started and it has kept the dust down to just a minimum.”*

### Price Wallance

Mendenhall, MS



30354 Tracy Road, Walbridge, OH 43465  
888-858-4425 • JHswash.com